



Specifications

Specifications:	
Part #	HX-P4805GD
Port Rate	10/100/1000 Mbps
Data pairs	All four (1/2, 3/6, 4/5, 7/8)
Power pairs	4/5 (+), 7/8 (-)
Cable length	40cm
Input Condition	AC100~240V 50/60Hz 0.6A max
Input Rated Voltage	100Vac~200Vac
Input Voltage Rate	90Vac~264Vac
Input Rated Frequency	50/60Hz
Input Frequency Range	47Hz~63Hz
Input Current	0.6A Max
Input Inrush Current	30A Max
Input No Load Power Consumption	0.5 Watt Max @ 115Vac/230Vac
Efficiency	80% Min
Rated Output Voltage & Current	48v/0.5A
Output Line Regulation	+/-1%
Output Load Regulation	+/-5%
Output Over Shoot	10% Max
Output Ripple and Noise	1% Max
Output Rising Time	20ms Max @ 115Vac
Output Hold-Up Time	8ms Min @ 230Vac
Protection	OCP OVP SCP OPP
Dielectric Withstand Voltage	3KV 5mA 60s
Leakage Current	0.25mA @ 230Vac
Dimension	90×50×30mm
Weight	96g
Operating Temperature Range	0°C ~ +40°C
Storage Temperature Range	-20°C ~ +85°C

Product Gallery

