



Specifications

Mechanical	
Dimensions	98 × 98 × 30 mm
Weight	320 g
Enclosure materials	Polycarbonate
Hardware	
Processor	Dual-core ARM® Cortex®-A53 at 1 GHz
Memory information	1 GB DDR3L
Management interface	Ethernet Bluetooth 5.1
Networking interface	(1) GbE RJ45 WAN port (1) GbE RJ45 LAN port
Power method	USB type C (5V/3A)
Supported voltage range	100–240V
Max. power consumption	3.83W
Operating temperature	-10°C to 40°C
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC
Gateway Features	
Performance	WiFi QoS with UniFi APs Application, domain, and country-based QoS Application and device type identification Additional internet failover with LTE Backup Internet quality and outage reporting
Next-generation security	Application-aware firewall rules Signature-based IPS/IDS threat detection Content, country, domain, and ad filtering VLAN/subnet-based traffic segmentation Full stateful firewall
Advanced networking	License-free SD-WAN* WireGuard, L2TP and OpenVPN server OpenVPN client OpenVPN and IPsec site-to-site VPN One-click Teleport* and Identity Enterprise VPN** Policy-based WAN and VPN routing DHCP relay Customizable DHCP server IPv6 ISP support *When paired with a Cloud Key or Official UniFi Hosting. **When paired with a Cloud Key.



Product Gallery

